

## **Product Data Sheet**

## Non Woven Geotextile (NW70-GP170)

GeoProducts NW70-GP170 is a needle-punched nonwoven geotextile made of 100% polypropylene staple
fibers, which are formed into a random network for dimensional stability. GeoProducts NW70-GP170 resists
ultraviolet deterioration, rotting, biological degradation, naturally encountered basics and acids.
Polypropylene is stable within a pH range of 2 to 13. GeoProducts NW70-GP170 is NTPEP certified and meets
requirements as per AASHTO Standards and/or D.O.T. Standards. GeoProducts NW70-GP170 meets or
exceeds the physical property values listed below:

PROPERTY	TEST METHOD MARV ENGLISH AVERAGE	
Tensile Strength (Grab)	ASTM D-4632	180lbs
Elongation	ASTM D-4632	50%
Puncture	ASTM D-4833	475lbs
Mullen Burst	ASTM D-3786	330psi
Trapezoidal Tear	ASTM D-4533	75lbs
UV Resistance (at 500 hours)	ASTM D-4355	70%
Apparent Opening Size (AOS)	ASTM D-4751	100 US Std. Sieve
Permittivity	ASTM D-4491	1.4 sec-1
Water Flow Rate	ASTM D-4491	105 gpm/ft2
Roll Sizes	12.5' x 360' 15' x 300'	3.81m x 109.8m 4.57m x 91.5m

\*Maximum average roll value

Exclusion of Liability

Information contained in this publication is accurate to the best of the knowledge of GeoProducts Holdings, LLC. The above values are Typical which is an average of the samples taken on this fabric and should not be used as minimum of maximum values unless stated otherwise. Any information or advice obtained from GeoProducts other than by means of this publication and whether relating to GeoProducts materials, is also given in good faith. However, it remains at all times, the responsibility of the customer to ensure that GeoProducts materials are suitable for the particular purpose intended.

Landscaping made easy. Savings made simple.

Concrete – Erosion & Sediment Control – Geotextiles – Hardscapes – Pipe & Drainage GeoProducts Holdings, LLC - 161 Technology Park Drive - P.O. Box 880 - Kilmarnock, VA 22482 Phone: (804)435-7777 - <u>sales@geoproductsllc.com</u>